



Mark Scheme (Results)

Summer 2026

Pearson Edexcel International Advanced Level

In Mechanics M3 (WME03)

Paper 01

Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at www.edexcel.com or www.btec.co.uk. Alternatively, you can get in touch with us using the details on our contact us page at www.edexcel.com/contactus

Pearson: helping people progress, everywhere

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at:

www.pearson.com/uk

Summer 2026

Question Paper Log Number P79480A

Publication Code WME03_01_2606_MS

All the material in this publication is copyright

© Pearson Education Ltd

General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

EDEXCEL IAL MATHEMATICS

General Instructions for Marking

1. The total number of marks for the paper is 75.
2. The Edexcel Mathematics mark schemes use the following types of marks:
 - **M** marks: Method marks are awarded for 'knowing a method and attempting to apply it', unless otherwise indicated.
 - **A** marks: Accuracy marks can only be awarded if the relevant method (M) marks have been earned.
 - **B** marks are unconditional accuracy marks (independent of M marks)
 - Marks should not be subdivided.

3. Abbreviations

These are some of the traditional marking abbreviations that will appear in the mark schemes and can be used if you are using the annotation facility on ePEN.

- bod – benefit of doubt
- ft – follow through
- the $\checkmark$ symbol will be used for correct ft
- cao – correct answer only
- cso – correct solution only. There must be no errors in this part of the question to obtain this mark
- isw – ignore subsequent working
- awrt – answers which round to
- SC: special case
- oe – or equivalent (and appropriate)
- d... or dep – dependent
- indep – independent
- dp decimal places
- sf significant figures
- * The answer is printed on the paper or ag- answer given
- $\square$ or d... The second mark is dependent on gaining the first mark

4. All A marks are 'correct answer only' (cao.), unless shown, for example, as A1 ft to indicate that previous wrong working is to be followed through. After a misread however, the subsequent A marks affected are treated as A ft, but manifestly absurd answers should never be awarded A marks.
5. For misreading which does not alter the character of a question or materially simplify it, deduct two from any A or B marks gained, in that part of the question affected. If you are using the annotation facility on ePEN, indicate this action by 'MR' in the body of the script.
6. If a candidate makes more than one attempt at any question:
 - If all but one attempt is crossed out, mark the attempt which is NOT crossed out.
 - If either all attempts are crossed out or none are crossed out, mark all the attempts and score the highest single attempt.
7. Ignore wrong working or incorrect statements following a correct answer.

General Principles for Mechanics Marking

(N.B. specific mark schemes may sometimes override these general principles)

- Rules for M marks:
 - correct number of terms
 - dimensionally correct
 - all terms that need resolving (i.e. *multiplied* by cos or sin) are resolved
 - only terms that need resolving are resolved
 - +/- errors are condoned
 - sin/cos confusion is condoned
- Omission or extra g in a resolution is an accuracy error not method error.
- Omission of mass from a resolution is a method error.
- Omission of a length from a moments equation is a method error.
- Omission of units or incorrect units is not (usually) counted as an accuracy error.
- DM indicates a dependent method mark, i.e. one that can only be awarded if a previous specified method mark(s) has been awarded.
- Any numerical answer which comes from use of $g = 9.8$ should be given as a decimal to 2 or 3 SF.
- Use of $g = 9.81$ should be penalised once per (complete) question.
 - N.B. Over-accuracy or under-accuracy of correct answers should only be penalised once per complete question. However, premature approximation should be penalised every time it occurs.
- Marks must be entered in the same order as they appear on the mark scheme.
- In all cases, if the candidate clearly labels their working under a particular part of a question i.e. (a) or (b) or (c)...then that working can only score marks for that part of the question.
- Accept column vectors in all cases.
- Misreads – if a misread does not alter the character of a question or materially simplify it, deduct two from any A or B marks gained, bearing in mind that after a misread, the subsequent A marks affected are treated as A ft

Question Number	Answer	Mark	Additional Guidance
1a	Use of $a = v \frac{dv}{dx}$ or $a = \frac{d}{dx} \left(\frac{1}{2} v^2 \right)$	M1	Use correct substituted form for a using given function (not just stating $a = v \frac{dv}{dx}$ oe).
	$a = \frac{qx}{(x^2 + 4)^3}$ condone $a = \frac{p}{(x^2 + 4)^3}$	M1	Power going down by 1 but condone error in chain rule if x is lost from numerator. M0 for just differentiating v wrt x .
	$a = \frac{-72x}{(x^2 + 4)^3}$	A1	Or equivalent unsimplified. Allow for evaluation of correct expressions of v and $\frac{dv}{dx}$ and attempt to multiply.
	Deceleration $= \frac{216}{2197} = 0.098... (\text{ms}^{-2})$	A1	2 sf or better. Must be positive.
		(4)	
1b	$\frac{dx}{dt} = \frac{6}{x^2 + 4}$	M1	Form differential equation in x and t using given v
	$\int x^2 + 4 dx = \int 6 dt$	M1	Separate variables to get polynomials and attempt to integrate (at least one power increasing). 6 could be on either side
	$\frac{1}{3} x^3 + 4x = 6t (+C)$	A1	Or equivalent. Condone missing constant of integration
	Use $x = 3, t = 0 \Rightarrow C = 21$	DM1	Correct use of limits to find constant of integration and use of $x = 6$ to find T (or as limits in a definite integral) E.g. $c = \frac{7}{2}$ with 6 on other side Dependent on both previous M marks.
	$T = 12.5$	A1	Accept $t = 13$
		(5)	
		(9)	

Question Number	Answer	Mark	Additional Guidance
2a	M(A)	M1	Or equivalent to obtain an equation in T . Dimensionally correct. Condone sin/cos confusion
	$T \times 3a \sin \theta^\circ = Mg \times \frac{3a}{2} \cos(2\theta^\circ)$	A1	Correct unsimplified equation. Allow consistently cancelled a
	$\Rightarrow \text{tension} = \frac{Mg \cos(2\theta^\circ)}{2 \sin \theta^\circ} \quad *$	A1*	Obtain given answer from correct working. Withhold if length a never seen in working.
		(3)	
2b	Extension in the string $= 2 \times 3a \cos \theta^\circ$	B1	Or for finding BC E.g. $\sqrt{18a^2(1 + \cos 2\theta^\circ)}$ E.g. $\frac{3a \sin 2\theta^\circ}{\sin \theta^\circ}$
	$T = \frac{\frac{2}{5}Mg \times "6a \cos \theta^\circ"}{3a}$	M1	Correct use of Hooke's Law for their extension in terms of a and $\theta/2\theta$ (must be an extension: $BC \pm 3a$ is M0)
	Form an equation in either 2θ or θ	M1	e.g. $\frac{4}{5}Mg \times \sin(2\theta^\circ) = Mg \cos(2\theta^\circ)$
	$\tan 2\theta^\circ = \frac{5}{4} \quad *$	A1*	Obtain given answer from correct working. Condone missing degrees symbol.
		(4)	
		(7)	

Question Number	Answer	Mark	Additional Guidance
3a			
	Resolve vertically	M1	Dimensionally correct. Condone sine / cosine confusion but angles and tensions must be different (allow same letter only if recovered).
	$T_A \cos \theta = 0.1g + T_B \cos \alpha$ $\left(\frac{12}{13} T_A = 0.1g + \frac{4}{5} T_B \right)$	A1	Correct unsimplified equation.
	Circular motion	M1	Dimensionally correct. Condone sine / cosine confusion but angles and tensions must be different (allow same letter only if recovered).
	$0.1r\omega^2 = T_A \sin \theta + T_B \sin \alpha$ $\left(0.675 = \frac{5}{13} T_A + \frac{3}{5} T_B \right)$	A1 A1	Unsimplified equation with at most one error Correct unsimplified equation
	Substitute for trig and ω and solve for T_B	DM1	Dependent on the two previous M marks
	$T_B = \text{tension} = 0.29 \text{ or } 0.286 \text{ (N)}$	A1	2 sf or 3 sf only (only penalise over-accurate "correct" answer once per whole question)
		(7)	
3b	Resolve horizontally and vertically	M1	Dimensionally correct. Condone sine / cosine confusion. Must be using $T_B = 0$ but allow inequality in working.
	$T_A \cos \theta = 0.1g$	A1	Correct unsimplified equation

	$0.1 \times 0.15 \omega^2 = T_A \sin \theta$	A1	Correct unsimplified equation
	$\omega = 5.2$ or 5.22	A1	2 sf or 3 sf only (only penalise over-accurate “correct” answer once per whole question)
		(4)	
		(11)	

Question Number	Answer	Mark	Additional Guidance
4a	Use of $\pi \int xy^2 dx \left(= \pi \int 25x - x(x+3)^2 dx \right)$ for moments about the y -axis	M1	Condone if π is missing. There must be some attempt to use the function in the question, not just quoting the general formula. E.g. $\pi \left(\int 16x - 6x^2 - x^3 \right) dx$
	Integrate as far as $\pi \left[\frac{25}{2}x^2 - \frac{x}{3}(x+3)^3 + \int \frac{1}{3}(x+3)^3 dx \right]$	M1	Or equivalent. Condone sign slips and slips in coefficients. Condone if π is missing
	Obtain $\pi \left[\frac{25}{2}x^2 - \frac{x}{3}(x+3)^3 + \frac{1}{12}(x+3)^4 \right]$	A1	Or equivalent e.g. $\pi \left[8x^2 - 2x^3 - \frac{1}{4}x^4 \right]$
	$= \pi \left\{ 50 - \frac{2}{3} \times 125 + \frac{1}{12} \times 625 - \frac{1}{12} \times 81 \right\}$ $(= 12\pi)$	M1	Correct use of limits 0 and 2. Must see at least 12 or 12π . Condone if π is missing
	Complete method for centre of mass	M1	Using their moment and the given volume (if they try to work out the volume it must be correct including correct sign). Allow the π to be missing from the given volume for the M mark.
	$= 12\pi \times \frac{3}{52\pi} = \frac{9}{13} *$	A1*	Obtain given answer from full and correct working but allow missing dx throughout.
	If π is missing from the moments integral, can score M marks only unless they have also worked out the volume and explicitly shown that π cancels.		
		(6)	
4b	Use of $\frac{3r}{8} = \frac{3}{2}$	B1	Correct distance for c of m of hemisphere seen or implied.
	Moments about AB	M1	Or equivalent. Dimensionally correct
	$\frac{3}{2} \times \frac{128}{3} \pi - \frac{9}{13} \times \frac{52}{3} \pi = d \times \left(\frac{128}{3} - \frac{52}{3} \right) \pi$	A1	Correct unsimplified equation in d
	$d = \frac{39}{19} *$	A1*	Obtain given answer from correct working. Allow with $\bar{x}$ etc. in place of d
			π is a common factor.

			Allow full marks if not seen.
		(4)	
4c	$\tan \theta^\circ = \frac{39}{19} \div 4 \quad \left(= \frac{39}{76} \right)$	M1	Correct use of trig to find a relevant angle. Allow for reciprocal.
	$\theta = 27$	A1	Or better 27.1649.... Must be in degrees.
		(2)	
		(12)	

Question Number	Answer	Mark	Additional Guidance
5a	Use of $EPE = \frac{\lambda x^2}{2a}$	B1	Correct form seen at least once
	Energy equation	M1	Dimensionally correct. Need all 3 terms
	$\frac{\lambda \times (2a)^2}{2a} = mg \times \frac{5}{2}a + \frac{\lambda (\frac{a}{2})^2}{2a}$	A1	Correct unsimplified equation
	$\frac{15\lambda a}{8} = \frac{5mga}{2} \Rightarrow \lambda = \frac{4}{3}mg$ *	A1*	Obtain given answer from full and correct working. Must see at least one line of working e.g. combining epe terms.
		(4)	
5b	Conservation of energy	M1	Dimensionally correct. Need all 3 terms
	$\frac{1}{2}mv^2 + mg \times 2a = \frac{4}{3}mg \times \frac{(2a)^2}{2a}$	A1 A1	Unsimplified equation with at most one error Correct unsimplified equation
	$\Rightarrow v = \sqrt{\frac{4ag}{3}}$	A1	Any equivalent form Eg. $\frac{2\sqrt{3ag}}{3}$ Accept $1.2\sqrt{ag}$ or better
		(4)	
5c	At max speed $T = mg$	M1	Form equation for equilibrium
	$\Rightarrow mg = \frac{4mg}{3} \times \frac{x}{a}$	A1	Correct unsimplified equation
	$\Rightarrow x = \frac{3}{4}a, \quad AE = x + a = \frac{7}{4}a$ *	A1*	Obtain given answer from full and correct working with no errors. Allow without “AE = ”
		(3)	
5c Alt1	Form equation using energy when extension is x and maximise v .		Forms equation for energy at an arbitrary point and then tries to find the value of their x which maximise v or v^2 (e.g. completing the square or differentiating). Note their “ x ” could be any

			consistently used position e.g. AP or DP .
	$\frac{4mg(2a)^2}{3 \times 2a} = \frac{4mg(x)^2}{3 \times 2a} + mg(2a - x) + \frac{1}{2}mv^2$ $v^2 = -\frac{4g}{3a}x^2 + 2gx + \frac{4}{3}ag$		Correct unsimplified equation
	$v_{\max} \text{ when } x = \frac{3}{4}a \Rightarrow AE = \frac{7}{4}a *$		Obtain given answer from full and correct working with no errors. Allow without “ $AE =$ ”
5c Alt2	Max speed at equilibrium position and as this is a spring that position is halfway between the positions where $v = 0$	M1	Observes that max speed occurs at equilibrium position and justifies use of midpoint by stating either: - it is a spring / never slack or - P moves with SHM and attempts to find midpoint
	$AE = \frac{\frac{1}{2}a + 3a}{2}$	A1	Correct unsimplified equation
	$AE = \frac{7}{4}a *$	A1*	Obtain given answer from full and correct working with no errors. Allow without “ $AE =$ ”
		(3)	
5d	Equation of motion	M1	Must be using distance from E
	$m\ddot{y} = mg - \frac{\frac{4mg}{3}\left(y + \frac{3}{4}a\right)}{a}$	A1	Correct unsimplified equation using distance from E (condone if using x again; allow “ a ” etc. for acceleration for this mark).
	$\Rightarrow m\ddot{y} = -\frac{4mg}{3a}y, \quad \ddot{y} = -\frac{4g}{3a}y$ Of the form $\ddot{y} = -\omega^2 y$ so SHM *	A1*	Obtain given answer from full and correct working. Requires a conclusion mentioning “SHM” and acceleration must be second derivative of displacement from E wrt t .
		(3)	
		(14)	

Question Number	Answer	Mark	Additional Guidance
6a	Conservation of energy P to Q	M1	Dimensionally correct. Required terms and no others.
	$\frac{1}{2}mv^2 = mg \times 1.5 \quad (\Rightarrow v^2 = 3g)$	A1	Correct unsimplified equation. No need to substitute the value for m .
	Circular motion at Q :	M1	Dimensionally correct. Required terms and no others
	$R - mg = \frac{mv^2}{1.5}$	A1	Correct unsimplified equation.
	$(\Rightarrow R = mg + 2mg)$ $R = 5.9$ or 5.88 (N)	A1	2 sf or 3 sf only. Accept $0.6g$
		(5)	
6b	Conservation of energy e.g. from P to R : $\frac{1}{2}mv^2 = mg \times 0.75$	M1	Dimensionally correct. Required terms and no others. Q to R : $\frac{1}{2}mv^2 + mg \times 0.75 = \frac{1}{2}m(3g)$
	$v^2 = 1.5g \Rightarrow v = \sqrt{1.5g}$	A1	oe
	Equation for time from R to S	M1	Complete method using <i>suvat</i> Condone sin/cos confusion.
	e.g. $-0.75 = \sqrt{1.5g} \sin 60^\circ t - 4.9t^2$	A1	Correct unsimplified equation
	$t = 0.856$	A1	0.86 or better seen or used $\left(\frac{\sqrt{210} + 3\sqrt{10}}{28} = 0.85636... \right)$
	Equation in terms of t for the horizontal distance after leaving R	M1	e.g. $\sqrt{1.5g} \cos 60^\circ t$ Condone sin/cos confusion.
	Complete method for distance QS	M1	e.g. $1.5 \sin 60^\circ + \sqrt{1.5g} \cos 60^\circ t$ or equivalent. Condone sin/cos confusion.
	$QS = 2.9$ or 2.94 (m)	A1	2 sf or 3 sf only
		(8)	
		(13)	
	Some useful values:		Other useful times: R to top of parabola: $\frac{3\sqrt{10}}{28} = 0.33881...$ Top of parabola to S : $\frac{\sqrt{210}}{28} = 0.51754...$

	$\sqrt{3g} = \frac{7\sqrt{15}}{5} = 5.42217\dots$ $\sqrt{1.5g} = \frac{7\sqrt{30}}{10} = 3.83405\dots$ $v_y = \frac{21\sqrt{10}}{20} = 3.32039\dots$ $v_x = \frac{7\sqrt{30}}{20} = 1.91702\dots$ $RS_{\text{horizontal}} = \frac{3\sqrt{7} + 3\sqrt{3}}{8} = 1.64167\dots$		
--	---	--	--

Question Number	Answer	Mark	Additional Guidance
7a	Max speed: $a\omega = 12$	B1	Seen or implied
	$(4\sqrt{5})^2 = \omega^2(a^2 - 2^2)$	B1	Correct use of $v^2 = \omega^2(a^2 - x^2)$
	Solve for a	M1	(N.B. $\omega = 4$)
	$a = 3$	A1	
		(4)	
7b	$A = a\omega^2 = 48$	B1ft	Follow their a , ω . May use $\frac{v_{\max}^2}{a}$. Do not need to see “ $A=$ ”
		(1)	
7c	Use $\ddot{x} = -A\cos\omega t$ or $\ddot{x} = -A\sin\omega t$ $\left(\frac{1}{2}A = \pm A\cos\omega t \text{ or } \frac{1}{2}A = \pm A\sin\omega t\right)$	M1	Or equivalent e.g. $x = a\cos\omega t$ and $\frac{1}{2}A = -\omega^2 x$ (N.B. $x = \pm\frac{3}{2}$)
	$4t = \cos^{-1}\frac{1}{2} \Rightarrow t = \frac{\pi}{12}$ or $4t = \sin^{-1}\frac{1}{2} \Rightarrow t = \frac{\pi}{24}$	A1	Obtain a relevant value of t (allow for an inequality)
	$\frac{2\pi}{\omega} - 4 \times \frac{\pi}{12}$ or $4 \times \frac{\pi}{24}$	M1	Complete method to obtain the required time
	$\frac{\pi}{6}$ (s)	A1	0.52 (s) or better (0.52359 ...)
		(4)	
		(9)	