

Cambridge International AS & A Level

PHYSICS

9702/52

Paper 5 Planning, Analysis and Evaluation

May/June 2024

MARK SCHEME

Maximum Mark: 30

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the May/June 2024 series for most Cambridge IGCSE, Cambridge International A and AS Level and Cambridge Pre-U components, and some Cambridge O Level components.

This document consists of **10** printed pages.

PUBLISHED**Generic Marking Principles**

These general marking principles must be applied by all examiners when marking candidate answers. They should be applied alongside the specific content of the mark scheme or generic level descriptions for a question. Each question paper and mark scheme will also comply with these marking principles.

GENERIC MARKING PRINCIPLE 1:

Marks must be awarded in line with:

- the specific content of the mark scheme or the generic level descriptors for the question
- the specific skills defined in the mark scheme or in the generic level descriptors for the question
- the standard of response required by a candidate as exemplified by the standardisation scripts.

GENERIC MARKING PRINCIPLE 2:

Marks awarded are always **whole marks** (not half marks, or other fractions).

GENERIC MARKING PRINCIPLE 3:

Marks must be awarded **positively**:

- marks are awarded for correct/valid answers, as defined in the mark scheme. However, credit is given for valid answers which go beyond the scope of the syllabus and mark scheme, referring to your Team Leader as appropriate
- marks are awarded when candidates clearly demonstrate what they know and can do
- marks are not deducted for errors
- marks are not deducted for omissions
- answers should only be judged on the quality of spelling, punctuation and grammar when these features are specifically assessed by the question as indicated by the mark scheme. The meaning, however, should be unambiguous.

GENERIC MARKING PRINCIPLE 4:

Rules must be applied consistently, e.g. in situations where candidates have not followed instructions or in the application of generic level descriptors.

GENERIC MARKING PRINCIPLE 5:

Marks should be awarded using the full range of marks defined in the mark scheme for the question (however; the use of the full mark range may be limited according to the quality of the candidate responses seen).

GENERIC MARKING PRINCIPLE 6:

Marks awarded are based solely on the requirements as defined in the mark scheme. Marks should not be awarded with grade thresholds or grade descriptors in mind.

Science-Specific Marking Principles

1 Examiners should consider the context and scientific use of any keywords when awarding marks. Although keywords may be present, marks should not be awarded if the keywords are used incorrectly.

2 The examiner should not choose between contradictory statements given in the same question part, and credit should not be awarded for any correct statement that is contradicted within the same question part. Wrong science that is irrelevant to the question should be ignored.

3 Although spellings do not have to be correct, spellings of syllabus terms must allow for clear and unambiguous separation from other syllabus terms with which they may be confused (e.g. ethane / ethene, glucagon / glycogen, refraction / reflection).

4 The error carried forward (ecf) principle should be applied, where appropriate. If an incorrect answer is subsequently used in a scientifically correct way, the candidate should be awarded these subsequent marking points. Further guidance will be included in the mark scheme where necessary and any exceptions to this general principle will be noted.

5 'List rule' guidance

For questions that require *n* responses (e.g. State **two** reasons ...):

- The response should be read as continuous prose, even when numbered answer spaces are provided.
- Any response marked *ignore* in the mark scheme should not count towards *n*.
- Incorrect responses should not be awarded credit but will still count towards *n*.
- Read the entire response to check for any responses that contradict those that would otherwise be credited. Credit should **not** be awarded for any responses that are contradicted within the rest of the response. Where two responses contradict one another, this should be treated as a single incorrect response.
- Non-contradictory responses after the first *n* responses may be ignored even if they include incorrect science.

6 Calculation specific guidance

Correct answers to calculations should be given full credit even if there is no working or incorrect working, **unless** the question states 'show your working'.

For questions in which the number of significant figures required is not stated, credit should be awarded for correct answers when rounded by the examiner to the number of significant figures given in the mark scheme. This may not apply to measured values.

For answers given in standard form (e.g. $a \times 10^n$) in which the convention of restricting the value of the coefficient (a) to a value between 1 and 10 is not followed, credit may still be awarded if the answer can be converted to the answer given in the mark scheme.

Unless a separate mark is given for a unit, a missing or incorrect unit will normally mean that the final calculation mark is not awarded. Exceptions to this general principle will be noted in the mark scheme.

7 Guidance for chemical equations

Multiples / fractions of coefficients used in chemical equations are acceptable unless stated otherwise in the mark scheme.

State symbols given in an equation should be ignored unless asked for in the question or stated otherwise in the mark scheme.

Question	Answer	Marks
1	Defining the problem	
	t is the independent variable and s is the dependent variable or vary t and measure s	1
	keep k <u>constant</u>	1
	Methods of data collection	
	labelled diagram of workable experiment including: <ul style="list-style-type: none"> • spring connected to magnet • vertical rule parallel to spring to determine s • rule held in position by a stand • stand resting on the bench • rule labelled and at least one other label from stand, clamp, card, (magnetic) sheet, (cylindrical) magnet, spring 	1
	$s = (\text{new}) \text{ length/position of spring} - \text{original length/position of spring}$	1
	use a micrometer to measure t	1
measure B using a (calibrated) Hall probe and rotate probe until <u>maximum</u> value or measure B using Hall probe first in one direction, then in the opposite direction and average	1	

Question	Answer	Marks
1	Method of Analysis	
	plot a graph of s against $\frac{1}{t}$ or equivalent (allow $\lg s$ against $\lg t$)	1
	relationship valid <u>if</u> a straight line that passes through the origin is produced (for $\lg s$ against $\lg t$: relationship valid <u>if</u> a straight line with gradient -1)	1
	$Z = \frac{k}{ALB} \times \text{gradient}$ (for $\lg s$ against $\lg t$: $Z = \frac{k \times 10^{\text{y-intercept}}}{ALB}$)	1

Question	Answer	Marks
1	<p>Additional detail including safety considerations</p> <p>D1 precaution related to <u>spring</u> and/or <u>magnet hitting eyes</u>, e.g. use of goggles/use of safety screen around experiment</p> <p>D2 keep A, L and B <u>constant</u></p> <p>D3 use a rule to measure L</p> <p>D4 micrometer/calipers to measure <u>diameter</u> d of the magnet and $A = \pi d^2 / 4$</p> <p>D5 description of method to determine k, e.g. add mass to spring and $k = mg / \text{extension}$ or use newton meter to measure force applied to spring and $k = \text{force} / \text{extension}$ or take several readings of force and extension, plot a force–extension graph and $k = \text{gradient}$</p> <p>D6 (magnetic) sheet clamped to bench</p> <p>D7 use pointer(s)/marker(s) on the spring to read off values from the rule</p> <p>D8 method to use video recorder and <u>replay</u> to determine maximum length of the spring or increase s or force <u>gradually/slowly</u> until magnet (just) leaves the card</p> <p>D9 repeat measurements of t in <u>different positions</u> on the card and average t or repeat measurements of s for each value of t and average s</p> <p>D10 method to check that the spring has not exceeded the elastic limit</p> <p>D11 use of non-magnetic stand or named non-magnetic material for stand, e.g. wood</p>	6

Question	Answer	Marks														
2(a)	gradient = n y-intercept = $\lg \frac{2}{C}$	1														
2(b)	<table border="1" data-bbox="772 402 1358 846"> <thead> <tr> <th data-bbox="772 402 1058 467">$\lg (L / \text{cm})$</th> <th data-bbox="1058 402 1358 467">$\lg (T / 10^{-5} \text{ s})$</th> </tr> </thead> <tbody> <tr> <td data-bbox="772 467 1058 532">1.73 or 1.732</td> <td data-bbox="1058 467 1358 532">1.38 or 1.380 ± 0.02</td> </tr> <tr> <td data-bbox="772 532 1058 597">1.85 or 1.845</td> <td data-bbox="1058 532 1358 597">1.51 or 1.505 ± 0.01</td> </tr> <tr> <td data-bbox="772 597 1058 662">1.93 or 1.934</td> <td data-bbox="1058 597 1358 662">1.59 or 1.591 ± 0.01</td> </tr> <tr> <td data-bbox="772 662 1058 727">2.033 or 2.0334</td> <td data-bbox="1058 662 1358 727">1.69 or 1.690 ± 0.02</td> </tr> <tr> <td data-bbox="772 727 1058 792">2.146 or 2.1461</td> <td data-bbox="1058 727 1358 792">1.81 or 1.806 ± 0.01</td> </tr> <tr> <td data-bbox="772 792 1058 846">2.223 or 2.2227</td> <td data-bbox="1058 792 1358 846">1.87 or 1.869 ± 0.01</td> </tr> </tbody> </table> <p data-bbox="302 873 1073 911">Values of $\lg (L / \text{cm})$ and $\lg (T / 10^{-5} \text{ s})$ correct as shown above.</p>	$\lg (L / \text{cm})$	$\lg (T / 10^{-5} \text{ s})$	1.73 or 1.732	1.38 or 1.380 ± 0.02	1.85 or 1.845	1.51 or 1.505 ± 0.01	1.93 or 1.934	1.59 or 1.591 ± 0.01	2.033 or 2.0334	1.69 or 1.690 ± 0.02	2.146 or 2.1461	1.81 or 1.806 ± 0.01	2.223 or 2.2227	1.87 or 1.869 ± 0.01	1
$\lg (L / \text{cm})$	$\lg (T / 10^{-5} \text{ s})$															
1.73 or 1.732	1.38 or 1.380 ± 0.02															
1.85 or 1.845	1.51 or 1.505 ± 0.01															
1.93 or 1.934	1.59 or 1.591 ± 0.01															
2.033 or 2.0334	1.69 or 1.690 ± 0.02															
2.146 or 2.1461	1.81 or 1.806 ± 0.01															
2.223 or 2.2227	1.87 or 1.869 ± 0.01															
	<p data-bbox="302 938 968 976">Uncertainties in $\lg (T / 10^{-5} \text{ s})$ correct as shown above.</p>	1														
2(c)(i)	<p data-bbox="302 1003 1436 1062">Six points from (b) plotted correctly. Must be within half a small square. Diameter of points must be less than half a small square.</p>	1														
	<p data-bbox="302 1092 1688 1153">Error bars in $\lg T$ plotted correctly. All error bars to be plotted. Total length of bar must be accurate to less than half a small square and symmetrical.</p>	1														

Question	Answer	Marks
2(c)(ii)	Straight line of best fit drawn. Do not accept line from top point to bottom point. Line must pass between (1.780, 1.45) and (1.800, 1.45) and between (2.085, 1.75) and (2.100, 1.75)	1
	Worst acceptable line drawn (steepest or shallowest possible line that passes through all the error bars). All error bars must be plotted.	1
2(c)(iii)	Gradient determined with clear substitution of data points into $\Delta y / \Delta x$. Distance between data points must be greater than half the length of the drawn line.	1
	Gradient determined of worst acceptable line with clear substitution of data points into $\Delta y / \Delta x$. uncertainty = (gradient of line of best fit – gradient of worst acceptable line) or uncertainty = $\frac{1}{2}$ (steepest worst line gradient – shallowest worst line gradient)	1
2(c)(iv)	y-intercept determined by substitution of correct point with consistent power of ten in m and x into $y = mx + c$.	1
	y-intercept of worst acceptable line determined by substitution into $y = mx + c$. uncertainty = y-intercept of line of best fit – y-intercept of worst acceptable line or uncertainty = $\frac{1}{2}$ (steepest worst line y-intercept – shallowest worst line y-intercept) Do not accept ECF from false origin method.	1

Question	Answer	Marks
2(d)	Value of n determined using gradient ($n = \text{gradient}$) and C given to 2 or 3 significant figures.	1
	Value of C determined using y -intercept with method shown. $C = \frac{2}{10^{y\text{-intercept}}}$	1
	Absolute uncertainties in n and C . uncertainty in $n = \text{uncertainty in gradient}$ and $\Delta C = C - \frac{2}{10^{\text{worst } y\text{-intercept}}} \text{ or } \Delta C = \frac{2}{10^{\text{min worst } y\text{-intercept}}} - \frac{2}{10^{\text{max worst } y\text{-intercept}}}$ Clear method must be shown with ΔC correctly evaluated.	1
2(e)	Value of L determined (non-zero) to a minimum of 2 significant figures from (c)(iii) and (c)(iv) or (d) with correct substitution and correct power of ten. Units of T and either C or y -intercept must be consistent. $\log L = \frac{\log T - \log \frac{2}{C}}{n} = \frac{\log 10 - y\text{-intercept}}{n}$ $L = 10^{\frac{\log 10 - y\text{-intercept}}{n}}$ or $L = \sqrt[n]{\frac{TC}{2}}$	1