



Mark Scheme (Results)

Summer 2026

Pearson Edexcel International Advanced
Subsidiary Level In Physics
WPH13/01

Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at www.edexcel.com or www.btec.co.uk. Alternatively, you can get in touch with us using the details on our contact us page at www.edexcel.com/contactus

Pearson: helping people progress, everywhere

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: www.pearson.com/uk

General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

Mark scheme notes

Underlying principle

The mark scheme will clearly indicate the concept that is being rewarded, backed up by examples. **It is not a set of model answers.**

1. Mark scheme format

- 1.1 You will not see 'wtte' (words to that effect). Alternative correct wording should be credited in every answer unless the MS has specified specific words that must be present. Such words will be indicated by underlining e.g. 'resonance'
- 1.2 Bold lower case will be used for emphasis e.g. '**and**' when two pieces of information are needed for 1 mark.
- 1.3 Round brackets () indicate words that are not essential e.g. "(hence) distance is increased".
- 1.4 Square brackets [] indicate advice to examiners or examples e.g. [Do not accept gravity] [ecf].

2. Unit error penalties

- 2.1 A separate mark is not usually given for a unit but a missing or incorrect unit will normally mean that the final calculation mark will not be awarded.
- 2.2 This does not apply in 'show that' questions or in any other question where the units to be used have been given, for example in a spreadsheet.
- 2.3 The mark will not be awarded for the same missing or incorrect unit only once within one clip in open.
- 2.4 Occasionally, it may be decided not to insist on a unit e.g. the candidate may be calculating the gradient of a graph, resulting in a unit that is not one that should be known and is complex.
- 2.5 The mark scheme will indicate if no unit error is to be applied by placing brackets around the unit.

3. Significant figures

- 3.1 Use of too many significant figures in the theory questions will not prevent a mark being awarded if the answer given rounds to the answer in the MS.
- 3.2 Too few significant figures will mean that the final mark cannot be awarded in 'show that' questions where one more significant figure than the value in the question is needed for the candidate to demonstrate the validity of the given answer.
- 3.3 The use of one significant figure might be inappropriate in the context of the question e.g. reading a value off a graph. If this is the case, there will be a clear indication in the MS.

- 3.4 The use of $g = 10 \text{ m s}^{-2}$ or 10 N kg^{-1} instead of 9.81 m s^{-2} or 9.81 N kg^{-1} will be penalised by one mark (but not more than once per clip). Accept 9.8 m s^{-2} or 9.8 N kg^{-1}
- 3.5 In questions assessing practical skills, a specific number of significant figures will be required e.g. determining a constant from the gradient of a graph or in uncertainty calculations. The MS will clearly identify the number of significant figures required.

4. Calculations

- 4.1 **use of** the formula means that the candidate demonstrates substitution of physically correct values, although there may be conversion errors e.g. power of 10 error.
- 4.2 If a 'show that' question is worth 2 marks, then both marks will be available for a reverse working. If the question is worth 3 marks then only 2 marks will be available.
- 4.3 The mark scheme will show a correctly worked answer for illustration only.

5. Quality of Written Expression

- 5.1 Questions that assess the ability to show a coherent and logically structured answer are marked with an asterisk.
- 5.2 Marks are awarded for indicative content and for how the answer is structured.
- 5.3 Linkage between ideas, and fully-sustained reasoning is expected.

Question Number	Answer	Additional Guidance	Mark
1(a)(i)	Either Use a tape measure (1) Ensure tape measure is straight/taut/tight (1) OR Use a trundle wheel (1) Ensure path is straight from student A to student B (1) OR Use a laser rangefinder (1) Ensure laser is horizontal (1) OR Use a rope/string that is straight between student A and student B (1) Measure length of rope/string with metre rule/tape measure (1)	Do not accept metre rule to measure D directly	2
1(a)(ii)	(Increasing distance) will have the same (absolute) uncertainty (1) Percentage uncertainty = absolute uncertainty/measured value ($\times 100\%$) (1) (measured value is bigger) so % uncertainty is smaller	Ignore references to resolution	2

1(b)(i)	EITHER There will be variation in the values (1) Or There is a reaction time Or Identify and remove anomalies (So repeat readings) allow a mean to be calculated to reduce (the effect of) random errors (1)	Ignore human error Not eliminate	2
1(b)(ii)	EITHER Record video to identify time when blocks hit (1) Analyse video for time when sound is detected (1) OR Use (2) microphone(s) and C.R.O. (1) Measure time between peaks on C.R.O (1) OR Use of an electronic starter eg two contacts on the pieces of wood to start timer (1) Use of an electronic stopper eg a microphone to stop timer (1)	Accept oscilloscope for CRO If only 1 microphone needs to be clear that an echo method is used for 2 marks	2
	Total for question 1		8

Question Number	Answer	Additional Guidance	Mark
2(a)(i)	EITHER Rubber/string may snap and may hit student's eye Wear goggles Or wear safety glasses Or wear eye protection OR Mass may fall and hit foot/feet Ensure feet aren't under the mass Or wear (safety) boots/shoes Or sand tray on floor	(1) (1) Not glasses alone (1) (1) Accept stand away Accept cushion	2
2(a)(ii)	Uses uncertainty = (half) the resolution Percentage uncertainty = 0.023 (%) to 1 or 2 sf	(1) <u>Example Calculation</u> (1) Resolution of digital caliper = 0.01 mm Percentage uncertainty = $(0.005 \text{ mm} / 22.13 \text{ mm}) \times 100$ % = 0.023 %	2
2(a)(iii)	Check (and correct) for zero error (on the calipers) To reduce systematic error MP2 dependent on MP1 Ensure caliper is close to/touching marks Or measure from centre of marks Or measure parallel to string/rubber band To reduce random error MP4 dependent on MP3	(1) Accept calibrate to zero (1) Accept eliminate (1) (1) Accept to reduce/eliminate parallax error by placing caliper close Do not accept eliminate random errors	4


2(b)(i)	Attempts to calculate the mean using all 5 values Mean $x = 22.4$ mm given to 1 d.p.	(1) (1)	<u>Example Calculation</u> Mean $x = (22.1 \text{ mm} + 22.5 \text{ mm} + 22.3 \text{ mm} + 22.4 \text{ mm} + 22.6 \text{ mm}) / 5$ Mean $x = 22.38$ mm	2
2(b)(ii)	Calculates half range for uncertainty Or Calculates furthest from the mean Percentage uncertainty in $x = 1.1$ (%) to 1 to 3sf (1.3(%) if max difference method used) Allow ecf for range and mean from 2(b)(i) for both marks	(1) (1)	<u>Example calculation</u> Range of repeats = $22.6 \text{ mm} - 22.1 \text{ mm} = 0.5 \text{ mm}$ Uncertainty in $x = 0.5 \text{ mm} / 2 = 0.25 \text{ mm}$ Percentage uncertainty in $x = (0.25 \text{ mm} / 22.4 \text{ mm}) \times 100 \% = 1.12 \%$	2
2(c)	Use of area under graph Energy for single square = 0.01 (J) Energy stored = 0.18 J to 0.20 J	(1) (1) (1)	Accept use of $\frac{1}{2} Fx$ <u>Example of calculation</u> 18-20 squares = 0.18 J to 0.20 J	3
Total for question 2				15

Question Number	Answer	Additional Guidance	Mark
3(a)	To give minimum current (1) Reduces chance of short circuit (1) Or Protects the ammeter	Allow reduces chance of overheating Ignore voltmeter	2
3(b)(i)	Max three from Inconsistent d.p. for current (1) The current at 0.74 V does not follow the trend (1) Insufficient readings (to draw a graph) (1) No evidence of repeats (1)	Allow sf Do not accept anomaly	3

3(b)(ii)	EITHER Use of 5% to determine lower limit of student's value of e.m.f. Use of $\varepsilon = 0.30 - C$ $\varepsilon = 1.04$ (V) which is outside range (of 1.07 V to 1.19V) so not zinc Or $C = -0.77$ (V) which is less than -0.74 (V) so not zinc OR Use of $\varepsilon = 0.30 - C$ Calculates percentage difference for value of e.m.f Percentage difference = 8.7 (%) which is greater than 5 (%) so not zinc	<u>Example calculation</u> (1) Range for students e.m.f = $1.13\text{V} \pm 5\% = 1.07\text{V}$ to 1.19V $\varepsilon = 0.30 - -0.74 = 1.04\text{V}$ (1) $\varepsilon = 1.04\text{V}$ which is outside range of 1.07 V to 1.19V so not zinc (1) <u>Example calculation</u> (1) $\varepsilon = 0.30 - -0.74 = 1.04\text{V}$ $\frac{1.13\text{V} - 1.04\text{V}}{1.04\text{V}} = 8.7\%$ (1) 8.7 % which is greater than 5% so not zinc (1)	3
	Total for question 3		8

Question Number	Answer	Additional Guidance	Mark
4(a)	Measure distance with a metre rule and time with a stopwatch Or Measure distance with a metre rule and time with light gates. Or Measure distance with a metre rule and use frame rate (of video) (1) Calculate v using $v=d/t$ (for each set) (1) Idea of measuring (distance and time) between at least 2 relevant pairs of points (1) If velocities are equal the parachute is at terminal velocity (1) MP4 dependent on MP3 Or If times for equal distances are equal, parachute is at terminal velocity	Accept measuring tape for metre rule Accept time(from video) for frame rate(of video)	4
4(b)(i)	Compares to $y = mx (+ c)$ and identifies gradient $= \frac{C\rho A}{2g}$ (1) Rearranges equation to $C = \frac{\text{gradient} \times 2g}{\rho A}$ (1)		2

4(b)(ii)	Correct values of v^2 ..rounded to 3 s.f.	(1)	Accept first row to 2 s.f.	2																					
		(1)																							
	<table><tr><td>m / kg</td><td>v / ms^{-1}</td><td>$(v^2 / \text{m}^2\text{s}^{-2})$</td></tr><tr><td>0.23</td><td>7.1</td><td>50(.4)</td></tr><tr><td>0.55</td><td>10.9</td><td>119</td></tr><tr><td>0.90</td><td>13.8</td><td>190</td></tr><tr><td>1.24</td><td>16.3</td><td>266</td></tr><tr><td>1.44</td><td>17.6</td><td>310</td></tr><tr><td>1.74</td><td>19.3</td><td>372</td></tr></table>	m / kg			v / ms^{-1}	$(v^2 / \text{m}^2\text{s}^{-2})$	0.23	7.1	50(.4)	0.55	10.9	119	0.90	13.8	190	1.24	16.3	266	1.44	17.6	310	1.74	19.3	372	
	m / kg	v / ms^{-1}			$(v^2 / \text{m}^2\text{s}^{-2})$																				
	0.23	7.1			50(.4)																				
	0.55	10.9			119																				
	0.90	13.8			190																				
	1.24	16.3			266																				
	1.44	17.6			310																				
1.74	19.3	372																							

4(b)(iii)	Labels axes with quantities and units Sensible scales Plotting Line of best fit	(1) Do not accept reversed axes or titles as quantity (unit). Accept $v^2 / (\text{ms}^{-1})^2$ on x-axis (1) Axes must cover at least half grid, value of 2cm square in 1, 2 or 5 only (2) Plots within 1 mm (1) Straight, plots on both sides of line, no rotation Accept graph in landscape 	
4(b)(iv)	Use large triangle (to calculate gradient)($4.7 \times 10^{-3} \text{ kgm}^{-2}\text{s}^2$) Uses gradient $= \frac{C\rho A}{2g}$ Value for C = 1.08 to 3 s.f. with no unit	(1) Min 160 on denominator or triangle shown on graph Data points from table must lie on line (1) <u>Example of calculation</u> $C = \frac{4.7 \times 10^{-3} \text{ kgm}^{-2}\text{s}^2 \times 2 \times 9.81 \text{ kgms}^{-1}}{1.21 \text{ kgm}^{-3} \times 0.0704 \text{ m}^2} = 1.0825$ (1)\ Range 1.06 to 1.10	3

4(c)	EITHER Factors other than A (and v) in the equation would be constant (1) (When A increases) v^2 must decrease (1) Or $A \propto 1/v^2$ v decreases by a factor of $\sqrt{2}$ (1) OR Drag would be greater (with larger area) at a given velocity (1) (Accelerates for) less time until drag equals weight (1) (When A increases) v^2 must decrease (1)	Accept equation in words	3
	Total for question 4		19